

FIG. 1




FIG. 2




FIG. 3




FIG. 4

. !

SW6	SW5	SW4	SW3	SW2	SW1	Switch States	PBUE	CHGEN	VINP1	Charging Current Signal	Lower voltage battery	USE B	USE_A	Signal States			-	
OFF.	OFF FR	양	2	윘	Q		low	high	high	₽	×	high	low	€	3	502		USE signals Indicate Batt
OFF	유	2	2	윢	<u>Q</u>		WO	high	high	high	×	high	Q.	€-	<u>-</u>	504		USE signals Indicate Battery A
OFF	2	었	유	윘	Q.		iow W	high	þigh	₩O₩	×	₩	high	€-	5	506		USE signals indicate Batt
8	2	유	양	유	ON	i	Q¥	high	high	rg Tg	×	low	high	€	<u>-</u>	508		USE signals indicate Battery 8
OFF	2	OFF	0	OFF	ON N		high	high	high	WO	×	lo w	ō,	Ę-	<u>, </u>	510		Use signals indicate Bat
S.	웆	온	2	양	오		high	high	high	high	×	Q₩	¥	€~	<u>, </u>	512		nals e Battery A
OFF.	유	유	S S	유	٥ ا		low	high	high	Wol	>	lOW	ē.	لرع	-	514	•	Use signals indicate Battery A and B in parallel
OFF	Q F	2	Q	유	오		WO	high	hígh	high	>	OW	O¥.	لع	-	516		arallel
OFF	2	윆	윢	우두	2	!	low	high	high	Įσ₩	æ	WO	ō.	لىع	-	518		
2	<u>Q</u>	유	OFF	OFF.	2		WO	high	high	high	В	low	low (لع	•	520		
OF S	OFF F	OFF	OFF	OFF	<u>Q</u>		low	WO	iow	₩O₩	×	high	rigir r	E	-	522	Battery A or B	Use signals Indicate neithe

		. SW4 SW5	SW1 SW2	VINP1 VINP2 BATTCOMP PBUE	Supply Mode	
•	:IG. 6	OFF ON	ON OF	high low		
·		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	ON OFF	low	1 8	
		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	OFF	high high high		

and the second of the second o





FIG. 7






FIG. 9